



# Weatherproof Stabilising Solution SS01

## Product Information

### DESCRIPTION

A solvent-based clear sealer for the pre-treatment of chalky, friable or porous masonry surfaces.

### USAGE/PURPOSE

To stabilise surfaces prior to the application of masonry paints and emulsion paints.

### CHARACTERISTICS

- Solvent-borne formulation

### PERFORMANCE

- Particularly suitable for treating surfaces of uneven absorption or high porosity
- Helps to ensure an even finish
- Maximises the coverage rate of the finish

### COLOUR

Almost colourless (*available with dye, to order*)

### ENVIRONMENTAL CONSIDERATIONS

Contains no added lead

### PACKAGING

**Can size:** 5 litres

### AVAILABILITY

Available from Glixtone stockists or to order from Glixtone Sales Department  
Tel: 0121 243 1122

## Technical Specification

### COMPOSITION

Flexible acrylic resins in white spirit.

### PROPERTIES

**VOC content:** Very high, greater than 50%

## Surface Preparation

Remove all flaking and loose material back to a sound surface. Make good any defective areas. Ensure all surfaces are clean, dry and firm.

### *If there is organic growth:*

Remove with a stiff bristle (not wire) brush and apply a liberal coat of Glixtone Fungicidal Wash: GS37.

## Application

### METHOD

Stir thoroughly before use. Apply by brush or spray.

### THINNING

Do not thin. Use straight from can.

### COVERAGE

Dependent upon the porosity and texture of the substrate. 6-8m<sup>2</sup> per litre on smooth, lightly powdering surfaces of average porosity.

### DRYING TIME

Dependent upon weather conditions and average temperature. Under normal conditions: 12 hours.

### CLEANING

Clean all brushes and spray equipment immediately after use with Glix 01 Thinners.

### LIMITATIONS

DO NOT use  
- Over creosote, tar or bitumen surfaces

# Weatherproof Stabilising Solution SS01

## Health & Safety Notes

Detailed information and guidance is provided in **Material Safety Data Sheet No. S1.2** The following represents important selected information only

**Warning:** this product is FLAMMABLE.  
Flash Point: 41°C

- Ensure good ventilation during application and drying
- Avoid contact with eyes and skin

### **In case of contact with eyes:**

Rinse immediately with plenty of water and seek medical advice

### **In case of contact with skin:**

Wash immediately with plenty of soap water or a proprietary skin cleanser

- Exclude sources of ignition during application and drying
- No smoking
- Keep out of reach of children
- When spraying:
  - Do not breathe spray
  - Wear suitable respiratory protective equipment

## STORAGE

Store in secure, dry conditions at temperature between 5° and 28°C. Protect from naked flame. Containers should be kept closed during storage. Avoid spillage and contamination. Do not empty into drains and water courses.

## SHELF LIFE

1 year in original, unopened container, if stored in accordance with recommendations above.

## Specification

Fully written model proprietary specifications for Glixtone products are available from the Glixtone Technical Services Department.

## Additional Information

### TECHNICAL ASSISTANCE

For further information, advice or guidance regarding any aspect of Glixtone products, please contact the Technical Services Department at the address below.

### REFERENCES

See also:

- Product Data Sheet No. 1.1  
**Fungicidal Wash: GS37**
- Material Safety Data Sheet No. S1.2

## WARRANTY

As Glixtone has no direct control over the methods employed by the user in applying its products, any warranty either written or implied, is given in good faith and can only cover the material itself.

## Glixtone Limited

Westminster Works  
Alvechurch Road  
West Heath  
Birmingham B31 3PG

Tel: +44 (0)121 243 1122  
Fax: +44 (0)121 243 1123  
E-mail: sales@glixtone.com



**CARR'S**  
PAINTS

A company approved to BS EN ISO 9001 Cert. No. FM 01467

© Glixtone Limited. All rights reserved. No part of this page may be copied, reproduced or transmitted in any form or by any means without written permission from the copyright holder

Weatherproof  
Stabilising Solution **SS01**