

PRODUCT SAFETY DATA SHEET for BR86

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY/UNDERTAKING

PRODUCT NAME BR86 GLASS / GLAZED SURFACE PRIMER
INTENDED USE For application by brush or low volume spray
SUPPLIER CARRS PAINTS UNIT 2E EAGLE ROAD NORTH MOONS MOAT REDDITCH B98 9HF
Emergency Tele 01527 599 460

2. COMPOSITION/INFORMATION OF INGREDIENTS

Substances presenting a Health or Environmental hazard within the meaning of the Chemicals (Hazard Information & Packaging) Regulations 1994 as amended.

Substance Name	CAS No.	EINECS No.	%age Range	Symbol letter	Risk Phrases*
XYLENE, MIXTURE OF ISOMERS WHITE SPIRIT/TURPENTINE SUBSTITUTE/STODDARD SOLVENT	1330-20-7	215-535-7	20 - 30 0 - 1	Xn,Xi Xn,N	20/21-38 20/21-36/37/38-51-53
SOLVENT NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY AROM.	101316-81-8	309-882-4	10 - 20	Xn	65
1,2,4-TRIMETHYLBENZENE	95-63-6	202-436-9	5 - 10	Xn,Xi,N	20-36/37/38-51/53

Symbols Key T+ - Very Toxic T - Toxic Xn - Harmful C - Corrosive Xi - Irritant N - Environmental
 * for full text of Risk Phrases see Section 16 'Other Information'

3. HAZARDS IDENTIFICATION

Hazard Symbols



Xn - Harmful



Irritant to Skin

Risk Phrases

Flammable

Harmful by inhalation, in contact with skin and may cause lung damage if swallowed

Irritating to eyes, respiratory system and skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Inhalation of vapours from this product can cause narcosis and, with continued exposure above the OEL, possible long term effects.

OTHER INFORMATION

4. FIRST AID MEASURES

GENERAL

In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION

Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

EYE CONTACT

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 mins. holding the eyelids apart, seek medical advice.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.

INGESTION

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

RECOMMENDED Carbon dioxide, Dry Powder, Sand, Foam.

NOT TO BE USED Water.

SPECIAL INSTRUCTIONS FOR FIRE FIGHTING PERSONNEL

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in sect. 7&8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth and place in suitable container for disposal in accordance with the waste regulations Do not allow to enter drains or water courses. If it does the local water company should be contacted immediately, in case of contamination of streams rivers or lakes the Environmental Agency. Clean preferably with a detergent, avoid use of solvents.

7. STORAGE & HANDLING

Storage

Observe the label precautions. Store between 5 & 25°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store away from oxidising agents and strongly alkaline or acid materials. Store in accordance with the HSE Guidance note "Storage of Flammable Liquids in Containers" HS(G) 51. The store room should be marked "Flashpoint below 32°C" in accordance with "The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 S.I. No 917 (1972) Sections 5 and 6.

Handling

Do not use in areas where potential sources of ignition exist. Use non sparking tools and exclude sources of heat, sparks and flames. Keep container tightly closed. Never use pressure to empty, container is not a pressure vessel. Always keep in containers made of the same material as the supply container. Avoid skin & eye contact. For personal protection see Sect.8. Good housekeeping, regular maintenance of spray booth filters, and regular removal of waste materials will minimise risks. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters may result in spontaneous combustion

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Substance Name	8hr LTEL		15min STEL		Notation
	ppm	mg/m3	ppm	mg/m3	
XYLENE, MIXTURE OF ISOMERS OEL's are XYLOL	100	435		650	Sk, OES
WHITE SPIRIT/TURPENTINE	100	575			OES
SUBSTITUTE/STODDARD SOLVENT OEL's are					
BENZENE BELOW 0.1% W/V					
1,2,4-TRIMETHYLBENZENE	25	125			OES

Notations = Sk - risk of absorption through skin Sen - respiratory sensitizer.

Notations = SK - Risk of absorption through skin SEN - Respiratory Sensitiser Bmgv - Biological Monitoring may be appropriate (see Biological Monitoring Guidance Value in EH40 Table 3)

OEL's are from EH40 except where marked SUP which are assigned by the supplier of the substance.

Engineering Measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If extraction methods are insufficient to maintain concentrations of particulates and/or solvent vapours below relevant OEL's, suitable respiratory protective equipment should be worn.

General Protection

All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

Respiratory Protection

Air fed respiratory equipment should be worn when spraying if levels cannot be controlled below OELs and engineering methods cannot be reasonably improved.

Hand Protection

Full physical protection is best. Seek relevant advice from glove manufacturers. Barrier cream may be of help but should not be applied after exposure has occurred.

Eye Protection

Eye protection designed to protect against liquid splashes should be worn.

Skin Protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap & water or a proprietary skin cleaner.

9. PHYSICAL & CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
FLASH POINT	=> 21 °C & <= 55°C Method: Equilibrium Method to ISO 1516 & ISO 3680
SPECIFIC GRAVITY	1.29 Method: Calculation
VAPOUR DENSITY	HEAVIER than Air
V.O.C. CONTENT	0.532Kgs/lit.
LOWER EXPLOSION LIMIT	0.8% vol
SOLUBILITY IN WATER	PARTIALLY MISCIBLE

10. STABILITY & REACTIVITY

Stable under the recommended storage & handling conditions (see Sect.7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and acid materials to prevent the possibility of an exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases unconsciousness. Splashes in the eyes may cause irritation and reversible local damage. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eye may cause irritation and reversible local damage.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution & Environmental Protection Acts.

14. TRANSPORT INFORMATION

Road/Rail

UN No.	1263
Packing Group	III
Class	3.3
Designation	PAINT

Sea

UN No.	1263
Class	3.3
Packing Grp.<=30lts	III
Packing Grp.>30lts	III
Marine Pollutant	No
Main Risk	FLAMMABILITY
Sub Risk	NARCOSIS
Shipping Name	PAINT

Air

UN/IATA ID Number	1263
Class	3.3
Packing Grp.<=30lts	III

Packing Grp.>30lts
Main Risk
Sub Risk
Shipping Name

III
FLAMMABILITY
NARCOSIS
PAINT

International Road/Rail

Item Number
Class
UN No.
Packing Group
Main Risk
Sub Risk
Shipping Name

31C
3
1263
III
FLAMMABILITY
NARCOSIS
PAINT

15. REGULATORY INFORMATION

The product is classified and labelled for supply in accordance with the Chemicals (Hazard Information & Packaging) Regulations as follows.

Classification



Xn - Harmful

Contains

XYLENE, MIXTURE OF ISOMERS
SOLVENT NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY AROM.

Risk Phrases

R10: Flammable
R20/21/65: Harmful by inhalation, in contact with skin and may cause lung damage if swallowed
R36/37/38: Irritating to eyes, respiratory system and skin.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety Phrases

S2: Keep out of reach of children
S13: Keep away from food, drink and animal feeding stuffs
S23: Do not breath vapour/spray
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28: After contact with skin, wash immediately with plenty of water.
S43: In case of fire do not use water.
S46: If swallowed seek medical advice immediately and show this container or label.
S7/9: Keep container tightly closed and in a well ventilated place
S24/25: Avoid contact with skin and eyes.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

'P' Phrases

Do not breathe Vapour or Spray

The information contained in this Safety Data Sheet does not constitute the user's own assessment of the workplace risks as required by other health & safety legislation.

The provisions of the Health & Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION

Text of any Risk Phrases listed in Section 2

R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R36/37/38	Irritating to eyes, respiratory system and skin.
R38	Irritating to the skin
R51	Toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R53	May cause long term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed

Date of Origination 30/11/94
Date of last revision 10/05/07

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information & Packaging) Regulations The product should not be used for purposes other than those shown in Section 1 without first

referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control the user is responsible for ensuring that the requirements of relevant legislation are complied with. TP-21

The information contained in this Safety Data Sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:-

The Control Of Substances Hazardous to Health Regulations 1994 (SI 1994: 3246)

The Manual Handling Operations Regulations 1992 (SI 1992: 2793)

Storage of Flammable Liquids in Containers. HS(G)51

Storage of Packaged Dangerous Substances. HS(G)71

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1988: 2839)